



Course Instructions

NOTE: The following two pages contain a preview of the final exam. This final exam is identical to the final exam that you will take online after you purchase the course.

After you purchase the course online, you will be taken to a receipt page online which will have the following link: [Click Here to Take Online Exam](#). **You will then click on this link to take the final exam.**

3 Easy Steps to Complete the Course:

- 1.) Read the Course PDF – download from our website
- 2.) Purchase the Course Online & Take the Final Exam – see note above
- 3.) Print Out Your Certificate

FINAL EXAM - 2010 ADA Standards for Accessible Design Part 2

1. According to 307.2, objects with leading edges more than 27 inches and not more than 80 inches above the finish floor or ground shall protrude ____ maximum horizontally into the circulation path.
 - a. 6 inches
 - b. 4 inches
 - c. 10 inches
 - d. 12 inches

2. The minimum maneuvering clearance at a manual swinging door, perpendicular to doorway, when the approach direction is from the front on the push side of the door, from table 404.2.4.1, is:
 - a. 48 inches
 - b. 60 inches
 - c. 36 inches
 - d. 24 inches

3. Advisory 404.2.7 indicates that hardware that requires simultaneous hand and finger movements requires greater dexterity and coordination:
 - a. and is preferred.
 - b. and is required as per Title X of the 1997 Act.
 - c. and should be used as required to match existing hardware.
 - d. and is not recommended.

4. From 408.4.1, elevator cars shall provide a clear width of 42 inches minimum and a clear depth of 84 inches minimum.

True
False

5. The radius of curvature at the leading edge of a stair tread shall be _____ maximum, as per 504.5.
 - a. 3/8 inch
 - b. 3/4 inch
 - c. 1/2 inch
 - d. 1 inch

6. From 608.7, thresholds in roll-in type shower compartments shall be _____ high maximum in accordance with 303.
 - a. 3/8 inch
 - b. 3/4 inch
 - c. 1/2 inch
 - d. 1 inch

7. The minimum character height for a horizontal viewing distance of less than 21 feet and ____ with a height to finish floor or ground from baseline of character of greater than 120 ____ inches, from table 703.5.5, is:
 - a. 5 inches
 - b. 2 inches
 - c. 8 inches
 - d. 3 inches

8. At least _____ of shelf space in storage facilities, according to 804.5, shall comply with 811.
- a. 50 percent
 - b. 35 percent
 - c. 60 percent
 - d. 10 percent
9. From 903.3, benches shall have seats that are 36 inches long minimum and 20 inches deep minimum and 24 inches deep maximum.
- a. True
 - b. False
10. As an exception to 1006.2, handrails shall not be required:
- a. at bus shelters.
 - b. on golf courses.
 - c. in amusement parks.
 - d. at pool lifts.