

Final Exam

- 1. The first State that was surveyed using the PLSS system was:
 - a. Maine
 - b. Ohio
 - c. Virginia
 - d. Texas
- 2. Government Lots are created in when the following conditions occur:
 - a. Along the north tier of a Township
 - b. Along Rivers and Lakes
 - c. Along Closing Lines
 - d. All of the Above
- 3. Original notes tell the surveyor:
 - a. The distance to the Corner
 - b. If a replat occurred
 - c. What was set for the corner
 - d. Both a and c
- 4. Which of the following corners are double proportioned?
 - a. Closing Corners
 - b. Section Corners
 - c. Quarter Corners
 - d. Meander Corners
- 5. Documentation on subsequent surveys can be found at:
 - a. Timber Companies
 - b. State Agencies
 - c. Register/Recorder Offices
 - d. All Above
- 6. Natural feature calls should be used to:
 - a. Support the corner's location
 - b. Set the corner
 - c. Ignored the calls
 - d. Refence the corner
- 7. Which of the following are examples of subsequent surveys that could be used to locate a corner?
 - a. A survey tied to the PLSS Corner
 - b. A reference mark with no ties to the PLSS Corner
 - c. A right of way plat with ties to a PLSS Corner
 - d. Both a and c

- 8. An obliterated corner is:
 - a. A corner that is missing but can be reestablished by other means
 - b. A corner that is found
 - c. A corner along a lake
 - d. A corner at a state line
- 9. Instruction to Surveyors Manuals can be found at:
 - a. County Surveyors Offices
 - b. Bureau of Land Management
 - c. Highway Departments
 - d. Register/Recorder's Offices
- 10. An obliterated corner can be remonumented based on information from the following documents:
 - a. Right of way plats that only reference the Section Line
 - b. GIS corner locations
 - c. Landowner testimony
 - d. Survey plats with no reference to the corner
- 11. Which of the following PLSS corners are double proportioned when they are considered lost?
 - a. Section Corners on Township Lines
 - b. Interior Section Corners
 - c. Quarter Corners
 - d. Section Corners on Range Lines
- 12. Which of the following PLSS corners are single proportioned when they are considered lost?
 - a. Quarter Corners
 - b. Meander Corners
 - c. Section Corners on Township Lines
 - d. Both a and c
- 13. Meander Corners were set:
 - a. At the intersection of section lines and rivers
 - b. At all Government Lot Corners
 - c. Periodically along the line
 - d. In the Lake
- 14. A method of calculating the bearing of a lost Meander Corner is:
 - a. Using the bearing of the east line of the Section
 - b. Calculating the weighted mean bearing
 - c. Using the record bearing from the original notes
 - d. Both b and c

15. Closing Corners are set:

- a. At the terminus of Section Lines
- b. At the intersection of a Section Line with a State Line
- c. At Rivers
- d. Both b and c